

SETUP

This screen contains all of the router's basic setup functions. Most users will be able to use the router's default settings without making any changes. If you require help during configuration, please see the user guide.

Host Name: (Required by some ISPs)

Domain Name: (Required by some ISPs)

Firmware Version: 1.40.1, Sep 10 2001

LAN IP Address: (MAC Address: 00-20-78-00-99-2D)

192 . 168 . 1 . 1 (Device IP Address)

255.255.255.0 (Subnet Mask)

WAN IP Address: (MAC Address: 00-20-78-00-99-2E)

Obtain an IP Address Automatically

Specify an IP Address 0 . 0 . 0 . 0

Subnet Mask: 255 . 255 . 255 . 0

Default Gateway Address: 0 . 0 . 0 . 0

DNS(Required) 1: 0 . 0 . 0 . 0

2: 0 . 0 . 0 . 0

3: 0 . 0 . 0 . 0

Login: PPPoE RAS Disable

NOTE: PPPoE is for ADSL user only.

RAS is for SingTel ADSL user only.

User Name: <username>

Password: <password>

RAS Plan: 512k Ethernet

Connect on Demand: Max Idle Time 5 Min.

Keep Alive: Redial Period 30 Sec.

Apply

Cancel

Help

FILTERS

Filters enable you to prevent certain PCs on your network from accessing your Internet connection.

Filtered Private IP Range:

(0 to 254)

- 1: 192.168.1. ~
- 2: 192.168.1. ~
- 3: 192.168.1. ~
- 4: 192.168.1. ~
- 5: 192.168.1. ~

Filtered Private Port Range:

(0 to 65535)

- 1: ~
- 2: ~
- 3: ~
- 4: ~
- 5: ~

Private MAC Filter

[Edit MAC Filter Setting](#)

- SPI: Enable Disable
- Block WAN Request: Enable Disable
- Multicast Pass Through: Enable Disable
- IPSec Pass Through: Enable Disable
- PPTP Pass Through: Enable Disable
- Remote Management: Enable Disable
- Remote Upgrade: Enable Disable

MTU: Enable Disable Size:

[Apply](#) [Cancel](#) [Help](#)